





## Label-Aire® 4000-TS Table Top Wrap

# The Label-Aire® Inline 4000-TS Table Top Wrap labeling system is designed to offer you advanced features while also making labeling easier, faster, and more affordable...making your operation more profitable.

The Inline 4000-TS's sheer flexibility allows you to build a labeling system to fit seamlessly in your production line. The Inline 4000-TS also delivers on Label-Aire's long-standing promise of advanced features, toughness, speed, and accuracy meaning lower operating costs and increased productivity for your business.

The 4000-TS Table Top is a compact, mobile version of the Inline 5100TS, designed to offer the same advanced functionality, but in a smaller, more flexible package. Its portability and efficient design make it the perfect solution for environments with limited space, ensuring reliable results and versatility.

Designed for reliable full- and partial wrap labeling at medium- to high speeds, high-volume, multi-shift operations, the tough and advanced Inline 4000-TS delivers.



### Inline 4000-TS Wrap Specifications

#### **Dimensions:**

Width: 31.5" (800 mm) Length: 43.3" (1100 mm) Height: 19.7" (500 mm)

#### Weight:

Approx. 330 lbs. (150 kg)

#### **Standard Label Dimensions:**

Web Width: 0.63" - 7.00" (20 mm -

178 mm) Label Length: 0.5" - 39" (25 mm -

450 mm)

#### **Label Packaging:**

12" (300 mm) O.D. rolls std. on 3" (76 mm) I.D. cores

#### **Conveyor Speed:**

Up to 750" (20m) per minute with Variable Frequency Drive (VFD)

#### Label Dispense Accuracy:

Up to +/- 1/32" (.8 mm)

#### Electrical:

120 Volts AC 60 Hz 16 Amps.

#### Air:

2 cfm at 60 psi to 90 psi required with imprinter option

Stated dimensions are approximations. Please consult factory if dimensions are required for line integration.

Main Drive:	Variable Frequency Drive (VFD)
Line Speed	up to 750" (24.4 m) per minute
Construction:	, , , , , , , , , , , , , , , , , , , ,
Frame	Stainless Steel
Cabinet	Stainless Steel
Conveyor:	
Width	0.011/450.4
	6.0" (152.4 mm)
Length	8' (2,438.98 mm) center line-to-center line
Height	19.7" (500 mm)
Static Eliminator:	lonizer to eliminate static build up from film labels
Operator Interface:	HMI Color Touch Screen
Control	Push Button Start/Stop for Conveyor
Metering Wheel:	Single
Drive	VFD
Wrap Belt:	7.0" (177.8 mm) Wide x 12.0" (304.8 mm) Long
Drive	VFD
Biivo	VI D

Consult factory for additional options.



#### **United States**

550 Burning Tree Road Fullerton, CA 92833 USA

o 714.441.0700

e info@label-aire.com

w www.label-aire.com

#### Europe

Via Bacchini 3/b 40026 Imola (BO), Italy

o +39.0542.1903925

e info@label-aire.com

www.label-aire.eu

© 2024 Label-Aire